

1

Sprinklers of long and medium throw driven by a turbine device

CHARACTERISTICS :

Sprinklers of middle or high capacity , for medium and high pressure systems , rotating at uniform speed over a full and part circle .

It is equipped with interchangeable nozzles of different size and an adjustable jet-breaker, providing an uniform distribution of rain all over the irrigated area. The singular evenness and lightness of watering make it particularly suitable for the irrigation of delicate plants, such as seedlings, flowers and vegetables .



Radius range
19 -78 (m)

Capacity range
5 -193 (m³/hr)

Pressure range
1.5 - 9 (atm)



CODE : 10002	
No. of Nozzles	2
Capacity (m ³ /h)	60 - 136
Radius (m)	46 - 64
Pressure (atm)	4 - 8
Connection	Flange

Polaris



CODE : 10003	
No. of Nozzles	2
Capacity (m ³ /h)	31 - 66
Radius (m)	36 - 54
Pressure (atm)	3 - 7
Connection	Flange

Big River



CODE : 10248	
No. of Nozzles	2
Capacity (m ³ /h)	15 - 52
Radius (m)	24 - 46
Pressure (atm)	2 - 6
Connection	2" female

Mercury



CODE : 10005	
No. of Nozzles	1
Capacity (m ³ /h)	5 - 30
Radius (m)	19 - 37
Pressure (atm)	2 - 6
Connection	1 1/2" female

River



CODE : 10246	
No. of Nozzles	2
Capacity (m ³ /h)	96 - 193
Radius (m)	56 - 78
Pressure (atm)	5 - 9
Connection	Flange

Gemini



CODE : 10251	
No. of Nozzles	2
Capacity (m ³ /h)	39 - 130
Radius (m)	42 - 67
Pressure (atm)	3 - 8
Connection	2 1/2" female

Mariner 2 velocity



CODE : 10165	
No. of Nozzles	2
Capacity (m ³ /h)	39 - 130
Radius (m)	42 - 67
Pressure (atm)	3 - 8
Connection	2 1/2" female

Mariner



CODE : 10134	
No. of Nozzles	2
Capacity (m ³ /h)	10 - 37
Radius (m)	22 - 41
Pressure (atm)	2 - 5
Connection	1 1/2" female

Skipper



CODE : 10415	
No. of Nozzles	2
Capacity (m ³ /h)	8 - 36
Radius (m)	19 - 41
Pressure (atm)	1.5 - 5
Connection	1 1/2" female

Luxor