

# 2

Impuls  
Sprinklers of  
long and  
medium  
throw

## CHARACTERISTICS :

Sprinklers of middle or high capacity , and pressure, rotating at full circle or parts circle , with slow return. Particularly suitable for all types of watering machines, can be used also for center pivots and normal installations . An intermittent and adjustable jet - breaker working only on the return , allows to get an uniform distribution of rain fall all over the irrigated area . Its operation , of entirely new conception , prevents any vibrations and counterstrokes, granting absolute safety to the user .

Radius range  
23 -78 (m)

Capacity range  
8 -170 (m<sup>3</sup>/hr)

Pressure range  
1.5 - 8 (atm)



CODE : 10342

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	58 - 170
Radius (m)	48 - 78
Pressure (atm)	3 - 8
Connection	Flange



CODE : 10343

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	58 - 170
Radius (m)	48 - 78
Pressure (atm)	3 - 8
Connection	Flange



CODE : 10420

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	44 - 138
Radius (m)	42 - 89
Pressure (atm)	3 - 8
Connection	Flange



CODE : 10353

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	26 - 83
Radius (m)	35 - 56
Pressure (atm)	3 - 6
Connection	3" female



CODE : 10381

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	9 - 44
Radius (m)	23 - 48
Pressure (atm)	1.5 - 6
Connection	2 1/2" female



CODE : 10417

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	9 - 44
Radius (m)	23 - 48
Pressure (atm)	1.5 - 6
Connection	2 1/2" female



CODE : 10441

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	8 - 57
Radius (m)	22 - 52
Pressure (atm)	2 - 6
Connection	2" female



CODE : 10337

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	31 - 102
Radius (m)	34 - 55
Pressure (atm)	3 - 7
Connection	3" female



CODE : 10164

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	31 - 115
Radius (m)	33 - 64
Pressure (atm)	2 - 7
Connection	3" female



CODE : 10178

No. of Nozzles	1
Capacity (m <sup>3</sup> /h)	9 - 44
Radius (m)	23 - 48
Pressure (atm)	1.5 - 6
Connection	2 1/2" female

